

FX-1500LCD-C

The Forza FX Series offers an enhanced level of protection, specially designed for your high-performance office equipment and entertainment components.



It features a coaxial surge protection line and LCD display, in addition to a battery-supported system (UPS), allowing you ample time to save your important information and shut down all your equipment safely during power failures. The FX UPS system comes in two different configurations: 1500VA and 2200VA.

Highlights

- Smart UPS with line interactive topology
- Emergency backup power supply
- Complete AVR protection
- System monitoring made simple with a state-of- the art LCD display
- Coaxial line protection
- Gigabit protection for networking, VoIP communication and modem devices
- ForzaTracker software
- USB cable included
- Trusted quality
- Backed by a 3- year warranty, limited to 2 years on batteries









Ideal for





- + Voltage regulator
- + Power back up

MPN	FX-1500LCD-C
General	4500/4/040/4
Capacity	1500VA/840W
Input	2221
Nominal voltage	200V
Voltage range	166-280VCA
Frequency	45-65Hz (autosensing)
AC plug style	Italian (CEI-23-50)
Output	
Nominal voltage	220V +/- 10%
Frequency	50/60Hz
Frequency stability	+/- 1Hz battery mode
Waveform	Modified sine wave
Total outlets	4 Italian (CEI-23-50) + 2 (IEC C 13)
Full battery / Surge protection outlets	4
Surge protection outlets only	2
Network protection	RJ-45 (supports gigabit speeds)
Phone/modem/fax protection	RJ-11
Coaxial protection	Included
USB management	Included
Battery	
Type and quantity	12V/9Ah (2)
Backup time	64 min **
Recharge time	6 hours to 90% after complete discharge
Voltage regulation	
Automatic voltage regulation	Included
Frequency regulation	
Automatic frequency selection	Included
Line/Battery transfer	
Typical transfer time	2-4ms
Low line transfer to battery (120/220V)	89VAC
High line transfer to battery (120/220V)	145VAC
Alarms/Indicators	
Visual indicators	Easy to read LCD with a blue backlight that displays the battery status, in
visual indicators	voltage, output voltage, and operation mode of the UPS
Audible	Battery mode: sounds every 10 seconds
Addible	Low battery: sounds every second
	Overload: sounds every 0.5 second
	Fault: continuous sound
Protection	i duit. Continuous souna
	Line mode: 110%+20%/-10%; shuts down after 5 minutes and goes to fa
Full protection	mode: 110%+20%/-10%; snuts down arter 5 minutes and goes to fault mode. 120%+20%/-10%; shuts down immediately and goes to fault mode.
loules	Battery mode:120%+20%/-10%; shuts down immediately
Joules	660J
Special features	to divide d
"Cold start" option	Included
Auto charge	Included
Environment	
Operating temperature	32-104° F
Storage temperature	5-113° F
Relative humidity	0-90% non-condensing
Audible noise	<40 dB at one meter

MPN	FX-1500LCD-C	
Physical appearance		
Power switch	Included (lighted)	
Housing	Flame retardant plastic	
Color	Black	
Cord length	3ft	
Dimensions	15.4x5.7x8.1in	
Weight	26.5lb	
Additional information		
Warranty	3 years*	

*2 years on batteries **Calculated with a single PC plus monitor at 12% load





















