

NT-512C/NT-752C/NT-1012C

Forza's NT series is designed to provide electric protection for your personal computer and peripherals.



With its compact size, the unit is ideal for small work spaces at the office or at home. Although small in size, it provides the maximum protection against the constant threat of electrical supply outages.

Highlights

- Uninterruptible power system
- Power protection for home and office equipment
- Automatic voltage regulator
- Boost and buck AVR to stabilize voltage
- 4 outlets to protect your devices
- Phone, fax and modem protection (RJ-11)
- Three-year warranty

NT-512C



500VA
PROTECTION LEVEL 5

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up



Ideal for

NT-752C



750VA
PROTECTION LEVEL 5

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up



Ideal for

NT-1012C



1000VA
PROTECTION LEVEL 5

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up



Ideal for

MPN	NT-512C	NT-752C	NT-1012C
General			
Capacity	500VA/250W	750VA/375W	1000VA/500W
Input			
Nominal voltage	220V	220V	220V
Voltage range	162-268VAC	162-268VAC	162-268VAC
Frequency	45-65Hz (autosensing)	45-65Hz (autosensing)	45/65Hz (autosensing)
AC plug style	Italian (CEI 23-50)	Italian (CEI 23-50)	Italian (CEI 23-50)
Output			
Nominal voltage	220V +/- 10%	220V +/- 10%	220V +/- 10%
Frequency	50/60Hz	50/60Hz	50/60Hz
Frequency stability	+/- 1Hz battery mode	+/- 1Hz Battery mode	+/- 1Hz battery mode
Waveform	Modified sine wave	Modified sine wave	Modified sine wave
Total outlets	4 Italian (CEI 23-50)	4 Italian (CEI 23-50)	4 Italian (CEI 23-50)
Full battery / Surge protection outlets	4	4	4
Phone/modem/fax protection	RJ-11	RJ-11	RJ-11
Battery			
Battery type and quantity	12V/4.5Ah (1)	12V/7Ah (1)	12V/9Ah (1)
Backup time	18 min.**	25min**	32 min**
Recharge time	4 hours to 90% after complete discharge	4 hours to 90% after complete discharge	4 hours to 90% after complete discharge
Voltage regulation			
High cutoff	268VAC +/- 5%	268VAC +/- 5%	268VAC +/- 5%
Boost	162-204V +/- 5%	162-204V +/- 5%	162-204V +/- 5%
Buck	236-268V +/- 5%	236-268V +/- 5%	236-268V +/- 5%
Low cutoff	162VAC +/- 5%	162VAC +/- 5%	162VAC +/- 5%
Frequency regulation			
Automatic frequency selection	Included	Included	Included
Line/Battery transfer			
Typical transfer time	2-4ms	2-4ms	2-4ms
Low line transfer to battery	162VAC +/- 5%	162VAC +/- 5%	162VAC +/- 5%
High line transfer to battery	268VAC +/- 5%	268VAC +/- 5%	268VAC +/- 5%
Alarms/Indicators			
Visual	AC mode: solid blue Battery mode: blinking blue Fault mode: blue light goes out	AC mode: solid blue Battery mode: flashing blue Fault mode: blue light goes off	AC mode: solid blue Battery mode: blinking blue Fault mode: blue light goes out
Audible	Battery mode: sounds every 10 seconds Low battery: sounds every second Overload: sounds every 0.5 second Fault: continuous sound	Battery mode: sounds every 10 seconds Low battery: sounds every second Overload: sounds every 0.5 second Fault: continuous sound	Battery mode: sounds every 10 seconds Low battery: sounds every second Overload: sounds every 0.5 second Fault: continuous sound
Protection			
Full protection	Voltage regulation, overload, discharge and overcharge protection	Voltage regulation, overload, discharge and overcharge protection	Voltage regulation, overload, discharge and overcharge protection
Joules	200J	200J	200J
Special features			
"Cold start" option	Included	Included	Included
Auto charge	Included	Included	Included
Environment			
Operating temperature	32-104°F	32-104°F	32-104° F
Storage temperature	-4-122°F	-4-122°F	-4-122°F
Relative humidity	0-90% non-condensing	0-90% non-condensing	0-90% non-condensing
Audible noise	<40dB at one meter	<40dB at one meter	<40 dB at one meter
Physical appearance			
Power switch	Push button	Push button	Push button
Housing	Fire retardant plastic	Fire retardant plastic	Flame retardant plastic
Color	Black	Black	Black
Cord length	3ft	3ft	3ft
Dimensions	11x4x5.6in	11x4x5.6in	11x4x5.6in
Weight	8lb	9.3lb	10.8lb
Additional information			
Warranty	3 years*	3 years*	3 years*

**Single PC plus monitor
*2 years on batteries

