forza POWER TECHNOLOGIES

forzaups.com

SL-1022UL-C

Line interactive smart UPS system with a multifunction LCD touchscreen display for real-time monitoring.



Forza's new SL series of smart UPS systems has been redesigned with a LCD touchscreen for ease of use through its user friendly interface which also displays power conditions in real time. The SL series counts with UL certification and is acomplete solution for government agencies or private businesses in the educational, financing and public sectors. The integration of voltage regulation, surge suppression and backup capabilities in a single unit has made this one of the best-selling UPS systems in its class. The UPS comes with ForzaTracker monitoring software to easily administer the unit directly from your computer through a USB communication port.

Highligts

- Touch screen LCD status display
- USB communication port with monitoring software
- Overload, discharge and overcharge protection
- Fire retardant plastic

1000VA

PROTECTION LEVEL 5

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up

50 minutes backup time

5 protected outlets

forza Tracker Monitoring software

Ideal for

Computers & accesories


Video surveillance

Small server

MPN	SL-1022UL-C
General	
Capacity	1000VA/600W
Input	
Nominal voltage	220V
Voltage range	162-268VAC
Frequency	45-65Hz (autosensing)
AC plug style	Italian
Included cable	One IEC C13 to CEI 23-50
Output	
Nominal voltage	220V +/- 10%
Frequency	50/60Hz
Frequency stability	+/- 1Hz Battery mode
Waveform	Modified sine wave
Total outlets	4 Italian (CEI 23-50) /1 IEC C13
Full battery with surge protection outlets	5
Network protection	RJ-45
Phone/modem/fax protection	RJ-11
USB management	Included with ForzaTracker software
Battery	
Battery type and quantity	12V/7Ah (2)
Backup time	50min**
Recharge time	4 hours to 90% after complete discharge
Voltage regulation	
High cutoff	268V +/- 5%
Boost 1	162-204V +/- 5%
Buck	236-268V +/- 5%
Low cutoff	162V +/- 5%
Frequency regulation	
Automatic frequency selection	Included
Line/battery transfer	
Typical transfer time	2-4ms
Low line transfer to battery	162VAC +/- 5%
High line transfer to battery	268VAC +/- 5%
Alarms/indicators	
Visual indicators (LCD display)	Easy to read touchscreen LCD with a blue backlight that displays input voltage, output voltage, battery capacity, load level, and UPS status
Audible tone	Battery mode: Sounds every 10 seconds Low battery: Sounds every second Overload: Sounds every 0.5 second Fault: Continuous sound
Protection	
Full protection	Voltage regulation, overload, discharge and overcharge protection
Joules	660J
Special Features	
"Cold start" option	Included
Auto charge	Included
Environment	
Operating temperature	32-104°F
Storage temperature	-4-113°F
Relative humidity	0-90% non-condensing
Audible noise	<40dB at one meter

MPN	SL-1022UL-C
Physical appearance	
Power switch	Push button
Housing	Flame retardant plastic
Color	Black
Dimensions	12.6x5.1x7.2in
Weight	17.6lb
Additional information	
Warranty	3 years*

* 2 years on batteries
** Single PC plus monitor



Forza Power Technologies, LLC. Forza® is a registered trademark. All rights reserved.
All other trademarks and brand names are registered trademarks of their respective owners. Specifications are subject to change without notice. Made in China.